



15610 Wright Bros. Dr. Addison, TX 75001 USA

Phone: 972-661-1166 Fax: 972-661-1144

[www.sportchutes.com](http://www.sportchutes.com)

*"World's leading authority on unique water toys"*

## SPORT CHUTES BODY HARNESS SPECIFICATIONS



- 2" NYLON webbing for straps and belt; straps three layers, each 7000 lb. test break strength
- 4" NYLON sling webbing for back strap and leg loops, 60,000 lb. test break strength
- 6" NYLON sling webbing for seat, 100,000 lb. test break strength
- 2" STAINLESS STEEL "D" rings for belt, 1500 lb. test break strength each
- 2" SPRING CLIPS 2200 lb. test each
- Each clip has Nylon seat belt webbing (6500 lb. test) buffer webbing internally to prevent wear and chafing
- Closed cell foam seat and back strap padding for comfort



## INSTRUCTIONS

- 1) Lay harness flat on ground with pads facing up
  - 2) Undo belt and lay flat
  - 3) Slip both legs through leg loops and pull up
  - 4) Pull back strap around small of back where a belt would go
  - 5) Cinch belt around waist and pull strap through both "D" rings and loop strap back through the top until snug
  - 6) Connect spring clips to rings on chute person is suspended from and check belt for tightness; make is snug!
  - 7) Put on life jacket over harness. NEVER PUT HARNESS OVER LIFEJACKET!
- ALWAYS BE SURE HARNESS IS A PROPER FIT FOR THE SIZE OF PERSON WHO IS WEARING IT. NEVER PUT ON A HARNESS LARGER OR SMALLER THAN NECESSARY. BE SURE ALL CONNECTION POINTS ARE TIGHT AND SECURE.

